

ELAKESIDE

ASSEMBLY INSTRUCTIONS

WIRE SECURITY CARTS



Parts Included

Qty	Description
4	Posts
4*	Post Collets
4	Casters
1	Top Shelf
1	Bottom Shelf
1	Door (Left)
1	Door (Right)
1	Top Back Panel
1	Bottom Back Panel
1	End Panel (Left)
1	End Panel (Right)
4	Post Insert (w/Screws)
12	Nuts

* Per shelf

WARNING

Always place heavy objects on the lowest shelf. Weight capacities are for weight evenly distributed. Be sure casters are replaced as soon as they are worn out.

Basic Cart Assembly

1. Insert casters into the posts. Tap with rubber mallet if necessary to be sure casters are seated securely.
2. Attach a post collet on each post in the second notch above the caster.
3. Slide the bottom shelf down all four posts, keeping shelf level with the ground. Push down onto the post collets until seated onto each post.
4. For 2-shelf models, proceed to Step 5. Or, add shelves to unit now before proceeding to Step 5.
5. Attach a post collet on each post in the top notch.
6. Slide the top shelf down all four posts, keeping shelf level with the ground. Push down onto the post collets until seated onto each post.
7. Insert metal post plug into top of each post.
8. Proceed to security cage assembly instructions below to create a security cart.

Security Cage Assembly

1. Add back panels - hang the top panel from the top shelf, aligning the top loops over the post screw holes.
2. Insert screws into holes and LOOSELY tighten, as they will be removed in Step 4.
3. Hang the bottom back panel from the top back panel, being sure to slide the wires down inside the bottom shelf.
4. Add end panels - remove the screw from the post in back and hang the end panel from the top shelf so that the loops house the back panel wires, then secure each with a nut.
5. Align top loops over the post screw holes; re-insert screws into holes and tighten.
6. Add door panels - facing the front edge of unit, install the left door FIRST and THEN the right door.
7. Slide door panel side wires into the loops of the end panels and secure each with a nut.
8. Remove screws in top of posts, align top loops over the post screw holes; re-insert screws into holes and tighten.
9. Doors will stay closed during transport. Add a padlock (not included) for extra security.